

"NW" Series

Stainless Steel Discharge Adapters



EPG's NW Stainless Steel Discharge Adapters are designed for leachate, monitoring and remediation piping applications. The discharge adapters fasten through a riser or sump wall to allow for quick and easy pump connections and disconnections.

Features include:

- ◆ Solid 316 Stainless Steel construction for "C" models. All others are 304 Stainless
- ◆ Insert and housing have tapered slide fittings and O-ring seals, to maximize liquid-tight slip joint sealing
- ◆ Designed for maximum service life and ease of maintenance
- ◆ Built in 90° elbow with blind top that has female threads to accept threaded pipe to facilitate easy removal
- ◆ Reduces the need for personnel to enter hazardous locations to make pump connections and disconnections
- ◆ EPDM gasket for inner and outer wall with a washer and lock nut to make a gas tight seal
- ◆ Extended length discharge allows adapter to fit through 0.25" to 3" material wall thickness
- ◆ 1", 1.25", 1.5", 2", and 3" NPT sized fittings for pump, lift-out, and discharge pipes

For more information, call EPG Companies Inc., your environmental solutions partner!

Sold By:

MODEL	"A"	"B"	Minimum I.D.
NW1SS	1" NPT	4"	8"
NW1.25SS	1.25" NPT	4"	8"
NW1.5SS-C	1.5" NPT	4"	8"
NW2SS-C	2" NPT	5"	8"
NW3SS	3" NPT	6.25"	12"

**Manufacturer of
Environmental &
Industrial Solutions**



Mailing Address
P.O. Box 427
Rogers, MN 55374

Corporate Offices
1990 County Road 81
Maple Grove, MN 55311
www.epgco.com
info@epgco.com

(763) 424-2613

(800) 443-7426

FAX: (763) 493-4812

Bulletin 0286