

January 2004

Stainless Steel Ball Valves

EPG Stainless Steel Ball Valves can be used to decrease flow and/or introduce artificial head in discharge piping systems. When a pump operates outside its recommended curve, damage will occur to the pump and/or motor. Setting the EPG Stainless Steel Ball Valve to the proper discharge flow will allow the pump to operate within the recommended pump curve.

- Full Ported
- PTFE Seals
- AISI 316 SS Ball
- Blowout Proof SS Stem
- Plastic Coated SS Handle
- 1000 PSI Non-Shock Cold Working Pressure
- -20 F to + 350 F
- Double Seals
- No Metal to Metal
- Handle Stops
- Removable Handle
- NPT Female x Female Ports



PART #	SIZE	LENGTH	WEIGHT (lbs.)
BV25SS	.25"	2.42"	.66
BV37.5SS	.375"	2.42"	.66
BV50SS	.50"	2.50"	.77
BV75SS	.75"	3.00"	1.28
BV100SS	1.00"	3.60"	2.29
BV125SS	1.25"	3.93"	3.40
BV150SS	1.50"	4.65"	4.98
BV200SS	2.00"	5.40"	8.38
BV250SS	2.50"	6.53"	15.00
BV300SS	3.00"	7.60"	25.36
BV400SS	4.00"	10.20"	50.72