

October 1994

Type "F" Discharge Hose

The EPG Type "F" Discharge Hose is a general purpose, flexible, gray helix hose used for suction, construction, mining, irrigation lines, wellpoint systems, liquid fertilizer transfer and leachate transfer in landfills. This PVC discharge hose, in general, shows excellent resistance to acids, alkalies, aqueous solutions of salts, and many organic solvents and oils. Plasticized PVC is attacked by certain chlorinated hydrocarbons, aromatics, esters, ketones, aldehydes, phenols, and strong oxidizing agents. This chemical resistance is based on tests of specimens conducted by completely submerging the hose sample in the listed chemical or reagent. In critical applications, it is suggested that greater reliance be placed on actual field experience or that testing be performed under conditions of stress, exposure, temperature and duration, which can be related to the anticipated application.

SERVICE TEMPERATURE

-4° F to 150° F static condition,
14° F to 104° F dynamic condition

SPECIFICATIONS

Available in lengths up to 100 feet. Longer lengths can be met by coupling 100 foot and shorter lengths together with Cam Couplers featured in this section (see Bulletin 3316).

Series	ID Inch	OD Inch	Working Pressure (psi)		Vacuum Rating Inch HG		Min. Bend Rad. Inch 68° F	Approx. Weight Lbs./100 ft.
			68° F	104° F	68° F	104° F		
F 075	.75	0.94	115	75	Full	28	3	17
F 100	1	1.26	90	65	Full	28	3	22
F 125	1.25	1.51	90	65	Full	26	4	32