

Oil / Water Separator



EPG Companies Inc. OS Series Oil / Water Separators are designed to produce an effluent concentration of 10 mg/l or less of oil droplets 30 micron and larger of non-emulsified, sheen free, free and dispersed oils. By virtue of the FLOPAK coalescing media, readily settleable solids can be removed.

Fiberglass Construction:

- ◆ Dion Resin Construction
- ◆ Integral Bonded Fiberglass Fittings
- ◆ Hopper Bottom For Solids
- ◆ Integral Oil Storage Chamber
- ◆ Integral Expandable Effluent Chamber
- ◆ One Piece Removable Cover
- ◆ Quick Release Cover Hardware
- ◆ Industrial Grade PVC Cover Gasket
- ◆ PVC Constructed Oil Skimmer
- ◆ FLOPAK Coalescing Media

Steel Construction:

- ◆ Carbon Steel Construction
- ◆ Hopper Bottom For Solids
- ◆ Integral Expandable Effluent Chamber
- ◆ One Piece/Sectional Removable
- ◆ Cover(s) with Hold Down Hardware

- ◆ Coal Tar Epoxy Internal Coating
- ◆ External Epoxy Coating
- ◆ Industrial Grade PVC Cover Gasket
- ◆ PVC Constructed Oil Skimmer
- ◆ FLOPAK Coalescing Media

Options Available:

- ◆ Influent Feed Package
- ◆ Effluent Pumpout Package
- ◆ Oil Pumpout Package
- ◆ Elevation Stand
- ◆ Effluent/Oil Level Switches
- ◆ L-Bracket Hold Downs
- ◆ Freeze Protection Package
- ◆ External Oil/Water Reservoirs
- ◆ Retpak Secondary Coalescer
- ◆ Oil Sight Glass Assembly (Fiberglass model)

Leachate Pumps ◆ Remediation ◆ Control Systems Integration ◆ Telemetry

Sold By:

**Manufacturer of
Environmental &
Industrial Solutions**



Mailing Address
P.O. Box 427
Rogers, MN 55374

Corporate Offices
19900 County Road 81
Maple Grove, MN 55311
www.epgco.com
info@epgco.com

Bulletin 6205

(763) 424-2613

(800) 443-7426

FAX: (763) 493-4812